

PVC SCH 40 CLEAR PIPE

PVC CLEAR  
PRESSURE PIPE  
SCHEDULE 40 - PLAIN END



TUYAUX SOUS PRESSION  
PVC CLAIRE  
PROGRAMME 40 - BOUT UNI

ALL PIPE IS NON-RETURNABLE

SIZE TAILLE MM	NOMINAL PIPE SIZE INCHES DIMENSION NOMINALE DE TUYAU (EN POUCES)	PART NUMBER NUMRO DE PIØCE	PRICE PER FT PRIX PAR PIEDS	OUTSIDE DIAM. DIAM. EXT.	INSIDE DIAM. DIAM. INT.	MINIMUM WALL PAROI MOYENNE	WEIGHT PER 100FT INTENSITÉ POIDS PAR 100 PIEDS	PRESSURE RATING AT 73.4°F PAQUETS DE PRESSION À 73,4°F	CRATE QTY. FEET CAISSE- QUANTIT PIEDS
12	1/2" X 10FT	R4-500	\$ 9.37	0.840	0.608	0.109	16	300	35
20	3/4" X 10FT	R4-750	\$ 12.28	1.050	0.81	0.113	22	240	25
25	1" X 10FT	R4-1000	\$ 17.87	1.315	1.033	0.133	32	220	25
32	1-1/4" X 10FT	R4-1250	\$ 24.14	1.660	1.364	0.140	43	180	20
40	1-1/2" X 10FT	R4-1500	\$ 28.74	1.900	1.592	0.145	52	170	16
50	2" X 10FT	R4-2000	\$ 38.60	2.375	2.049	0.154	69	140	12
65	2-1/2" X 10FT	R4-2500	\$ 66.65	2.875	2.445	0.203	109	150	6
75	3" X 10FT	R4-3000	\$ 82.51	3.500	3.042	0.216	144	130	6
100	4" X 10FT	R4-4000	\$ 125.35	4.500	3.998	0.237	203	110	5
150	6" X 10FT	R4-6000	\$ 210.40	6.625	6.031	0.280	354	90	1

8" & 10" Sch 40 - P.O.A.

SCH 80 AVAILABLE - P.O.A.

**NOTES:**

True schedule 40 dimensions.  
All sizes are in standard 10' lengths.  
All Clear Pipe is packed in polybags.  
Pipe has a UL 94 V-0 Rating.

**REMARQUES:**

Véritables dimensions du programme 40  
Toutes les tailles sont dans les longueurs 10' standard  
Toute la pipe claire est emballée dans les poly-sacs.  
La pipe a une estimation V-0 de l'UL 94.

## PVC SCHEDULE 40 CLEAR PIPE

Clear Schedule 40 Rigid PVC pipe – an outstanding choice for sight glass and dual containment applications carrying liquid and even some solids.

### Typical Applications for Clear Schedule 40 Rigid PVC Pipe:

#### PVC Compound

- |   |  |  |
|---|--|--|
| <ul style="list-style-type: none"> <li>• Conforms to FDA standards</li> <li>• Non-toxic</li> <li>• Non-conductive</li> <li>• Corrosion resistant</li> <li>• Underwriters Laboratories rating 94VO</li> <li>• Flame retardant</li> <li>• Resists bacterial and chemical activity</li> <li>• Superior transparency</li> </ul> | <ul style="list-style-type: none"> <li>• Medical/Hospital Uses</li> <li>• Sight Gauges</li> <li>• Dual Containment</li> <li>• Agriculture</li> <li>• Cosmetics</li> <li>• Pharmaceuticals</li> <li>• Fish Hatcheries</li> <li>• Bakery Products</li> <li>• Dairy Processing</li> </ul> | <ul style="list-style-type: none"> <li>• Environmental Applications</li> <li>• Beverage Processing</li> <li>• Chemical Processing</li> <li>• Electroplating</li> <li>• Food Processing (wet or dry)</li> <li>• Laboratory Applications</li> <li>• Photographs</li> <li>• Industrial Waste Treatment</li> </ul> |
|---|--|--|

PROPERTY	UNIT	VALUE	TEST METHOD
Cell Classification		12454B	ASTM D-1784
Specific Gravity ± .02	g/cm <sup>3</sup> @ 23°C	1.337	ASTM D-792
Hardness Shore D Instant ± 3		76	ASTM D-2240
Izod Impact (1/8" specimen) @ 73°F	ft.-lbs./inch of notch	0.76	ASTM D-256
Impact Resistance (falling weight) C-125 Impactor Configuration @ 73°F	ft.-lbs./inch	120	ASTM D-4226
Tensile Strength @ yield @ break	PSI	7094 4585	ASTM D-638
Modulus of Elasticity	PSI	435000	ASTM D-638
Elongation	%	36	ASTM D-638
Deflection Temperature under Flexural Load	°C @ 264 PS °F @ 264 PSI	71.5 160.7	ASTM D-648
Coefficient of Linear Expansion	/°C /°F	6.78 x 10 <sup>-5</sup> 3.77 x 10 <sup>-5</sup>	ASTM D-696
Flammability	Classification	V-O	UL-94

---

HYTEK PLASTIC SALES INC. 2175A TESTON ROAD, MAPLE, ONTARIO, L6A 1T3 TELEPHONE (877) 832-7977, FAX (888) 216-8926  
 ALL TAXES EXTRA • PRICES SUBJECT TO CHANGE WITHOUT NOTICE • F.O.B. STOCKING POINT MINIMUM BILLING \$50.00  
 HYTEK PLASTIC SALES INC. 2175A TESTON ROAD, MAPLE, ONTARIO, L6A 1T3 TELEPHONE (877) 832-7977, FAX (888) 216-8926  
 TOUTES TAXES EN SUS • PRIX SUJET A CHANGEMENT SANS PREAVIS • F.A.B. POINT D'ENTRE POSAGE FACTURE MINIMALE \$50.00